


Full Color Laser Distance 60M

7DM1160

- Colorful LCD display for easily reading
- Functions : Single measure, continuous measure, area, volume, height, stake-out
- Six flexible ways for height measurement
- Universal 8 length units with auto-converting
- 360° inclination sensor for determining the horizontal and vertical distance
- 2 selectable measurement reference points : Front and rear
- Automatic orientation display
- CE Approval IEC 60825-1: 2014, EN 61326-1: 2013



Technical data	
Display	Color LCD
Measuring Range	0.05 m ~ 60 m
Resolution	0.001 m
Accuracy	±1.5 mm
Laser Type	650 nm, Class II, < 1 mw
Unit(Selectable)	m, ft, in, 0'0" 1/32, 1/32in, 1/16in, 1/8in, 10/33
Battery Life	Up to 6,000 measures
Operation Temperature	-5° C ~ 40° C
Storage Temperature	-20° C ~ 60° C
Memory	50 set
IP code	54
Automatic Power-Off	Laser-120 seconds Device-180 seconds
Battery	AAA x 2 PC. Included



• Color LCD

Overview for device :


- A - LCD
- B - Single Measure
- C - Addition
- D - Subtraction
- E - Clear / Power
- F - Functions Included Single Measure, Continuous Measure, Area, Volume, Six Indirectly Height Measurements, Stake-out, Level, Unit and Setting
- G - Reference
- H - Receiving Lens
- I - Laser Emitted Window

KT NO.	Size (mm) L x W x H		
7DM1160	105 x 48 x 21	200	1 / 40

Measuring

79062

- Adjustable square measuring with angle spirit level 305mm
- Sliding combination of square, spirit level, height gauge and steel rule
- 90° and 45° level allow try-square and metre-square work
- Metal scriber pin in the end
- Metric and imperial marking at both sides
- Precision cast zinc alloy and stainless blade
- For woodwork



KT NO.	mm	Inch		
79062-12	305	12	312	12 / 72

