

Infrared Thermometer

9DN12

- Not necessary to contact with the object
- IR point can be displayed clearly
- °C and °F interchangeable functions
- Selection of different materials
- Dark screen backlight test board functions
- 15 seconds automatically turn off the screen
- 9V battery x 1 PC. (included)

Technical data

Temperature range	-30~550°C (-22~1022°F)
Operating temperature	0~50°C
Resolution	0.1°C / 0.1°F
Accuracy	±2.5% OR 3°C
Emissivity	Selectable (0.85 / 0.90 / 0.95)
Distance to spot ratio	12 : 1
Auto power off	15 seconds
Laser pointer	Class 2 Laser < 1 mW

KT NO.	Overall Size (mm)			
	L x W x H			
9DN12	193 x 47 x 126		313	5 / 20



Testing Screwdriver

6CB02

- Testing range : 100~250V
- CE approval
- Don't use the testing screwdriver as screwdriver
- Neon indicator



KT NO.					Testing range		
	mm	mm	mm	mm			
6CB02	3	0.6	65.5	140	100~250V	15	12 / 288

Digital Voltage Tester

6CB21

- Self-Diagnostic test
- Built-in LED flashlight
- LCD Display
- Protection IP64
- AAA 1.5V x 2 PC.
- Standard category :
EN 61243-3 / IEC 61243-3
EN 61010-1 / IEC 61010-1
CAT.III 690V / CAT.IV 600V

KT NO.	Overall Size (mm)			
	L x W x H			
6CB21	255 x 66 x 30		250	5 / 20

Specification

DC Voltage Test	12, 24, 50, 120, 230, 400, 690V
Polarity indication	Yes
AC Voltage Test	12, 24, 50, 120, 230, 400, 690V
Phase rotation test	Yes
High voltage indication	≥ 50V
Frequency range	0-70Hz
Continuity test	0~550KΩ
Operation condition	-10~55°C

