


Click Type Adjustable Torque Wrench

Industrial application with durability
 Loud click sound and strong impulse when required torque is reached
 Tolerance of torque $\pm 3\%$ (CW)
 Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
 Ideal for using on oily, chemical and noisy assembling working field
 CW/CCW Direction



Dual Scale - Kilogram-force Centimeter(kgf-cm)

KT NO.	Gear teeth	Square drive	Torque range kgf-cm	Incr.	Overall length mm	g	kg
3432F-1KF	24	3/8"	50-250 kgf-cm	2.5 kgf-cm	240	450	1 / 24
3432F-3KF	24	3/8"	200-1000 kgf-cm	10 kgf-cm	342	800	1 / 12
3442F-1KF	24	1/2"	200-1000 kgf-cm	10 kgf-cm	342	800	1 / 12
3442F-3KF	24	1/2"	400-2000 kgf-cm	20 kgf-cm	498	1500	1 / 12

Adjustable Torque Wrench

Design for easy torque adjustment
 Quality accords to DIN ISO 6789:2017 & ASME B107.300-2010
 Tolerance of torque $\pm 4\%$ (CW)
 CW/CCW Direction



- The production of injection molding helps it against come off
- One hand operation
- Quick torque set
- Automatic torque locking

Dual Scale - Newton Meter & English (N-m / ft-lb)

KT NO.	Gear teeth	Square drive	Torque range N-m / ft-lb	Incr.	Overall length mm	g	kg
34464-1FG	24	1/2"	40-210 N-m (33.2-151.2 ft-lb)	1.0 N-m	470	1250	1 / 12
34464-2FG	24	1/2"	70-340 N-m (62.7-239.7 ft-lb)	3.0 N-m	590	1590	1 / 12